


# Product data sheet

WAX 27° GREY 41W LED 4000K RA>80  
8246090672  
SG ARMATUREN



Design: Christian Hvidt Spot LED luminaire. IP66 simple LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Light grey or black frame treated for use outdoors. Direct optics with several solutions. Complete with LED driver for operation of LED light sources mounted to component rail. Pre-mounted with connecting cable (10 m). Prepared for mounting on a mast. Safety class II. Wax is as standard available with 13° and 27° reflector (45° reflector on request). Mast and wall consoles are not included but are sold separately. Light distribution Direct (Beam angle 27°) Light Technic LED 41W 4000K Ra>80 SDCM 2 L90/B10>100,000 at Ta=25°C Control gear On/Off Protection Class II IP66 IK07 Energy and approvals A++ CE Materials and finish Housing: Die-cast aluminum Colour: Grey (structure 2150 sablé) Optics: Glass Mounting/Connection Pole, wall, bollard or earthing rod, Outdoor Cable 2x1mm² 10m Wind projected area: 403cm² - Max 4 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	41 W	CRI	80
Total flux	3710 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	41 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 10.64 in  
Width: 7.10 in  
Height: 10.55 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 41 W  
Appliance Class: II

## Protection

IP: 66  
IK: 07