


Product data sheet

ELNM L11 MP LE3
ELISIAN MEDIUM EMERGENCY
DEXTRA




Elisian Medium - Ø223mm, IP40 Recessed downlighter with polycarbonate housing, four point steel spring mechanism and microprism diffuser. Options: LE3 - Lithium Emergency (419 lumens) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RCS - Reacta-Control Wireless Sensor RLS - Reacta-Link Wireless Sensor BL - Black Housing WH - White Housing

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	419 lm	LOR	100%
Luminous efficacy	140 lm/W	Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.5 W	CRI	80
Total flux	901 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	7.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 1.57 in
Diameter: 8.78 in

Adjustability

Rotatable, Tiltable

Electric

System power: 10.5 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 40

Designation labels: CE