
Product data sheet


LIGHTING PAD R 900 INDIREKT
556-666
HÄFELE



IP 20

Extremely effective sound-absorbing acoustic luminaire, 3 cable holders on top, tool-free adjustable, embossed front fleece, colour grey dawn, diameter 910 mm, additional MH-foam on the reverse for increased sound absorption (sound absorption class A), 12 Bartenbach lenses integrated in the front fleece, indirect light component on top for additional ceiling lighting, 46 % direct, 54 % indirect beam, direct light component with narrow beam, CRI > 90, including converter and operating device, dimmable via DALI/switchDim, the dimming unit is capable for video conferencing, indirect light separately switchable when using 2 DALI addresses, please order suspension set with supply cord separately according to your individual mounting situation (length 2 m: 555-713, length 4 m: 555-714). Front fleece available in further colours: far mountain, nightfall, soft moss, vineyard, white, yellow field, black ink.

Light output 1



1 x LED

Nominal lamp power	74.4 W	LOR	101%
Lamp flux	5900 lm	Total flux	5981 lm
Luminous efficacy	79 lm/W	Total power	74.4 W
CCT	4000 K		
CRI	92		

Mounting mode

Pendant

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in

Adjustability

Fixed

Design

Color of housing: Yellow, Red, Blue, White, Green, Anthracite / graphite

Electric

System power: 74.4 W

Protection

IP: 20