


Product data sheet

ALU-QUADRAT
251044.003.1
RZB




IP
43

IK
02

Series: Alu-Quadrat Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: jet black (RAL 9005) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 190, B 190, H 100 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 420lm System power: 9W Beam Angle: 146°/149° Unified Glare Ratio: 18,1 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	80
Total flux	420 lm	LOR	100%
Luminous efficacy	47 lm/W	ULOR	27%
		Total power	9 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.48 in
Width: 7.48 in
Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 9 W

Protection

IP: 43
IK: 02