



# Product data sheet

PRO-CEILING 30W, 300MM  
4000113X  
PROLUMIA




Light source: SMD LED's Color rendering index: Ra>80 Operating temperature: -10°C - +40°C Rated life hours: 35.000 - 50.000 LED driver(included): CE, TUV LED-current: 1000mA Input: 220-240Vac, 50/60Hz Power Factor: >0.90 Beam angle: 110°

## Light output 1




1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	2740 lm	Total flux	2740 lm
Luminous efficacy	91 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	85 lm/W	Total power	30 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	2370 lm	Total flux	2370 lm
Luminous efficacy	79 lm/W	Total power	30 W
CCT	2700 K		
CRI	80		

## Mounting mode

Ceiling mounted

## Electric

System power: 30 W  
Appliance Class: I

### Shape and measurements

Height: 1.54 in

Diameter: 11.81 in

### Protection

IP: 40

IK: 08

Designation labels: CE