

Product data sheet

LUCAS VIII (WALL FITTING BEADED)
9.828.3046.16
LEIPZIGER LEUCHTEN



IP
55


High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W | LOR | 80% |
| Lamp flux | 2000 lm | ULOR | 4% |
| Luminous efficacy | 27 lm/W | Total flux | 1600 lm |
| CCT | 3400 K | Total power | 59 W |
| CRI | 54 | | |



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W | LOR | 80% |
| Lamp flux | 4000 lm | ULOR | 4% |
| Luminous efficacy | 36 lm/W | Total flux | 3199 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in
Diameter: 22.44 in

Electric

System power: 59-89 W

Protection

IP: 55