




# Product data sheet

BARIS 40 LED Z 4450LM PRM I KL. IP20 860MM 840 39W BIALY  
925047  
LENA LIGHTING



925047 BARIS 40 LED Z 4450LM PRM I KL. IP20 860MM 840 39W BIALY Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). The optical system in the form of an opal cover. The optical system in the form of a prismatic diaphragm reduces glare and is characterized by a greater light transmittance than the opal diffuser, which has a direct impact on a higher value of luminous efficacy. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires to have 1.2m long slings in a set with a box.

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 39 W     | CRI         | 80     |
| Total flux         | 4450 lm  | LOR         | 100%   |
| Luminous efficacy  | 114 lm/W | Total power | 39 W   |

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 33.86 in

Width: 1.57 in

Height: 2.09 in

## Adjustability

Fixed

## Design

Material impression: Matt

Color of housing: White

## Electric

System power: 39 W

Ballast: ECG

Appliance Class: I

## Protection

IP: 20

IK: 03

Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: -13...95°F