


Product data sheet

TENTEC ZONO RECESSED LUMINAIRE, SYSTEM RING
TL1161216-03-40 + 81001R18
SCHMITZ | WILA



Tentec zono LED 4000 K Recessed Luminaire, Light distribution direct Downlight System Ring Product: TL1161216-03-40 Lite Optic: 81001R18 Lite Optic Filigree trim ring white with a bayonet fixing, tool free installation. Light Technique Integrated diffusor cup for homogenous light distribution Colour rendering index CRI > 80 Colour consistency <3-step MacAdams (SDCM) 50.000 h lifetime (L80/B10) Mirror reflector made of corrosion and age resistant pure aluminium (AL99.98), silk matt, dust repellent and fingerprint resistant Luminaire housing Robust housing made of die-cast aluminium Passive temperature management Operating and assembly technology LED driver integrated Driver suitable for connection to central battery systems Threaded multi-point fixing, for ceiling thicknesses 1-25mm MS-3 mounting technique for a tool-free change of Liteoptics Lamp Wattage: 24 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 2760 Lm System Efficiency: 102 Lm/W Luminance $\gamma \geq 65^\circ$: --- UGR: 25 Number Luminaires LZ: 0.05 Connector: plug-in terminal, 2 x 1.5 mm², with loop-in function Reflector Size: R18 Diameter D: 210 mm Cut-out CO: 195 mm Installation Depth RD: 130 mm Total Weight: 1.1 kg Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record TL1161216-03-40+81001R18

Light output 1



1 x General service incandescent lamp

Nominal lamp power	27 W	LOR	100%
Lamp flux	2760 lm	Total flux	2760 lm
Luminous efficacy	102 lm/W	Total power	27 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 5.12 in
Diameter: 8.27 in

Adjustability

Fixed

Electric

System power: 27 W
Appliance Class: II

Protection

IP: 20