


Product data sheet

LIGHTSOFT 1 BOLLARDS
SLH-10667-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - One IP68 connector supplied with 0.5 m of 3x1.0 sqmm outdoor cable - Durable silicone rubber gasket - Anodised, high-purity aluminium reflector - Clear, impact-resistant, UV-stabilised polycarbonate lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	12 W	CRI	80
Total flux	1124 lm	LOR	100%
Luminous efficacy	94 lm/W	Total power	12 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	13.6 W	CRI	80
Total flux	22 lm	LOR	100%
Luminous efficacy	2 lm/W	ULOR	9%
		Total power	13.6 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 39.37 in
Diameter: 7.32 in
Weight: 7.7 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 25.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C