Product data sheet


MINI SHOOTER
9901-Q-4-645-XX
UNILAMP



IP 67 IK 07

Description SHOOTER is a robust ground-surface uplighter constructed with a robust aluminium housing and use of a thick safety glass cover. It is suitable for installation where a typical in-ground uplighter cannot or should not be used. It is designed to operate with high power LED light source. SHOOTER is protected from dust, water and possible harmful impact. This luminaire can be used to illuminate columns, panels, blocks, and ceilings from the low level. It's perfectly matched in any architectural environment. Anchor unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 die-cast aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • High efficiency reflector. • M20 cable gland. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED

Nominal lamp power	13 W	LOR	100%
Lamp flux	1590 lm	ULOR	7%
Luminous efficacy	122 lm/W	Total flux	1590 lm
CCT	4000 K	Total power	16 W
CRI	80		

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Length: 6.50 in
Width: 6.50 in
Height: 5.99 in

Adjustability

Fixed

Electric

System power: 16 W
Controller: Dimmable 1..10V
Appliance Class: I

Protection

IP: 67
IK: 07