Product data sheet


MAGCARDO MAXI
722189.003
RZB



IP 20 IK 06

Series: MAGCARDO maxi Projector unit for tool-free mounting in separate recessed frame. Luminaire top: die-cast aluminium, powder-coated. Rotation range 356° and swivel range ± 35°. Inner cover prevents view into the false ceiling. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. Magnetic click locking mechanism for quick and convenient installation without tools: insert the recessed frame (1, 2 or 3-lamp) with clamp fastener (no tools required), push the luminaire head with the base plate into the recessed frame and fix magnetically. Separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.Modular design: recessed mounting frame must be ordered separately! Colour: deep black, matt (RAL 9005) Length: 172 mm Width: 167 mm Height: 137 mm Recess height: 155 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 92 System power: 25 W Rated luminous flux: 3250 lm Beam angle Down: 65° Luminous efficiency: 130 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	90
Total flux	3250 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	13%
		Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.57 in
Width: 6.77 in
Height: 5.39 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Black

Electric

System power: 25 W

Protection

IP: 20
IK: 06