



# Product data sheet

LTUB60 SU SF 1120 1500 NW OPAL BS  
L61SS112LOOP940N4  
LAMP



Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI 90. Built-in electronic ON/OFF control gear. With IP20, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

## Light output 1



1 x LED			
Nominal lamp power	12.9 W	LOR	100%
Lamp flux	1038 lm	Total flux	1038 lm
Luminous efficacy	80 lm/W	Total power	12.9 W
CCT	4000 K		
CRI	90		

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 45.35 in  
Width: 2.76 in  
Height: 2.56 in

## Adjustability

Fixed

## Design

Color of housing: Black, White

## Electric

System power: 12.9 W  
Appliance Class: I

## Protection

IP: 20  
IK: 07