Product data sheet


BRISA-L2WG6-LC-O3-24LED-4000K-3000LM-19.1W
LIGHTRONICS



IP 66 IK 10

BRISA FUNCTIONALLY COMPLETE From residential streets to access roads: the BRISA makes it possible to illuminate the entire living environment with a single luminaire line. The BRISA has specific variants for crossings, cycle paths and for protecting flora and fauna. This versatility makes the BRISA line suitable for business parks, industrial estates, ecological zones, parking spaces, large car parks, cycle paths, roundabouts, holiday parks, footpaths and residential areas. All the luminaires in the BRISA line are impact-resistant (IK 10) and waterproof (IP 66).

Light output 1



24 x LED

Nominal lamp power	0.796 W	LOR	100%
Lamp flux	125 lm	ULOR	3%
Luminous efficacy	157 lm/W	Total flux	3000 lm
CCT	4000 K	Total power	19.1 W
CRI	70		

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 23.62 in
Width: 9.45 in
Height: 5.12 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Black, Anthracite / graphite, Silver gray

Electric

System power: 19.1 W

Protection

IP: 66
IK: 10