Product data sheet


MEDO®
1011852
SLV



IP 20 IK 03


The MEDO® HYVE 40 is a surface-mounted ceiling luminaire designed for indoor use. It is equipped with a light source offering a colour temperature of 3000 or 4000 Kelvin and a beam angle of 80°. The luminaire features DALI-2 dimming as well as touch control, enabling flexible light adjustment. The housing is made of aluminium and steel, ensuring a robust and durable construction. With a diameter of 38 centimetres and a height of 6 centimetres, the luminaire has a compact design. The IP20 protection rating indicates protection against solid foreign objects, but no protection against water. The MEDO® HYVE 40 is suitable for professional applications requiring reliable and controllable ceiling lighting.

Light output 1



1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	2124 lm	Total flux	2124 lm
Luminous efficacy	135 lm/W	Total power	15.7 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	15.6 W	LOR	100%
Lamp flux	2131 lm	Total flux	2131 lm
Luminous efficacy	137 lm/W	Total power	15.6 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.96 in
Width: 14.96 in
Height: 2.39 in
Weight: 2.8 kg

Adjustability

Fixed

Electric

System power: 15.6-15.7 W
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 03