



Product data sheet

110 TUBE0 LED TUBULAR LIGHT FITTING
110 15L60 H50 PC DV P3X2,5 (11000 1150)
SCHUCH



LED tubular light fitting, TUBE0, 38 W, 6160 lm, 162 lm/W, Class I, IP68 (3m), IPX9K, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -25 °C/+50 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Tube PC clear, Closure Stainless steel (1.4571), Through wiring (DV) 3x2.5 mm² PVC, for food areas, stainless steel pipe clamps included. LED tubular light-fitting TUBE0 with impact-resistant clear PC tube Ø 100mm, stainless steel locking caps, foamed silicone gasket and special element for length compensation. Powder-coated sheet steel reflector with Zhaga LED modules, frosted LED covers for glare limitation and ECG with overload and short circuit protection. Electrical connection by connection plug (FastConnect), male connector pre-installed, female with strain relief attached. Two stainless steel pipe clamps included. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1700,00 mm, Width/Diameter 133,00 mm, Height 117,00 mm, Net weight 5,29 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38 W	CRI	80
Total flux	6160 lm	LOR	100%
Luminous efficacy	162 lm/W	ULOR	7%
		Total power	38 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 66.93 in
Width: 5.24 in
Height: 4.61 in

Adjustability

Fixed

Electric

System power: 38 W
Appliance Class: I

Protection

IP: 68
IK: 10
Designation labels: CE