Product data sheet


MAX MINI ROUND
BA12-P2V8S1BBI8
LEDSC4



IP 67 IK 04

LedsC4 Max Mini Round BA12-P2V8S1BBI8 Recessed uplighting for outdoor use. Metres of cable included: 1. Structure material: Stainless steel AISI316, Aluminium. Structure finish: Gun Metal PVD. Diffuser material: Glass. Diffuser finish: Transparent. UV protection. Warranty: 5 Years. Product net weight (Kg): 0.14 Product width or diameter (mm): 47 Product height (mm): 35 Ø of the hole for recessing (mm): 33 Class 3. IP: IP66-IP67. IK: IK04. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Maximum power of light source: 2.2W. Colour temperature: 2700K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 16.9. Photobiological risk: RG2. Real flux (lm): 163. Real lm/W: 74. Voltage: 3. Equipment included: No, but it is needed. Total power: 2.2.

Light output 1



1 x LED

Nominal lamp power	2.5 W	LOR	100%
Lamp flux	163 lm	Total flux	163 lm
Luminous efficacy	65 lm/W	Total power	2.5 W
CCT	2700 K		
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 1.85 in
Width: 1.85 in
Height: 1.38 in

Adjustability

Fixed

Electric

System power: 2.5 W
Appliance Class: III

Protection

IP: 67
IK: 04