


Product data sheet

VEKTER 5 STREET AND AREA LIGHTING LUMINAIRES
VK-90001-M-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Maximum wind load resistance is 140 km/h - Surge protection 10 kV

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 36.5 W | CRI | 80 |
| Total flux | 5060 lm | LOR | 100% |
| Luminous efficacy | 139 lm/W | Total power | 36.5 W |

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 12.56 in
Width: 10.24 in
Height: 11.97 in
Weight: 7.6 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 36.5 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C