


Product data sheet

ATLANTIC LED II O CG-S
40071355604
EATON EMERGENCY LIGHTING



• LED safety luminaire with high protection class (IP66) for indoor and outdoor use • An integrated pressure equalization membrane reduces the effects of condensation in changing weather conditions • Luminaire with limited surface temperatures for use in operating areas with fire hazard • Acc. HACCP suitable for use in food processing industry (not Outdoor Wall) • Robust construction from aluminium diecast and high impact resistant cover made of polycarbonate • Numerous knock-outs for cable entries and double terminal for through-wiring (Outdoor Wall only one cable entry) • High spacing by double optics technology and highly efficient HighPower LEDs • Up to 28 m from luminaire to luminaire with optics for exit route illumination • Minimum service requirement due to high service life of the LEDs (up to 50.000 hours) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditures by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6000 K
Nominal lamp power	3.9 W	CRI	65
Total flux	260 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	3.9 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.93 in
Width: 5.35 in
Height: 2.44 in

Adjustability

Fixed

Electric

System power: 3.9 W
Suitable for feed-through wiring
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 66
IK: 09