


Product data sheet

FLAT POLYMERO
672133.002.7
RZB




IP
40

IK
03

Item Number: 672133.002.7 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, single battery system as standard with automatic self-test, status display on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, , H 120mm Lamp: LED + LED 1.5 W Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 8h Emergency Lighting System: automatic self-test Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 22W Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	2050 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	10%
		Total power	19 W

Mounting mode

Wall mounted

Electric

System power: 19 W

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Protection

IP: 40
IK: 03

Adjustability

Fixed