


Product data sheet

CENTRYXX
671840.002.1.07
RZB




IP
20

IK
05

Item Number: 671840.002.1.07 Series: Centryxx Type of Protection: IP 20 Protection Class: I Voltage: 230 V / 50 - 60 Hz Housing die-cast aluminium powder-coated, transparent plastic lens for wide-surface lighting, converter and storage battery integrated. Single battery system with integrated self-test and feedback through Dali bus only to the RZB 985405 monitoring system. Lamps (LED) included in delivery. Available Colours: white Type of Installation: Ceiling mounting Dimensions: L 180, B 180, H 32mm Lamp: LED Colour Temperature: 6500K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: DALI-Sibe Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 170lm System power: 4,2W Beam Angle: 126° Unified Glare Ratio: 33,1

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	4.2 W	CRI	80
Total flux	170 lm	LOR	100%
Luminous efficacy	40 lm/W	Total power	4.2 W

Mounting mode

Ceiling mounted

Electric

System power: 4.2 W

Shape and measurements

Length: 7.09 in
Width: 7.09 in
Height: 1.26 in

Protection

IP: 20
IK: 05

Adjustability

Fixed