


Product data sheet

POWERSION 7 RECESSED LOW BAY LUMINAIRES
PWV-80001-EW-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38.1 W	CRI	80
Total flux	4940 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	100%
		Total power	38.1 W

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Length: 18.90 in
Width: 18.90 in
Height: 11.81 in
Weight: 6.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 38.1 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 07
Surface temperature: 40°C