


Product data sheet

WALL MOUNTED LUMINAIRE LIVORNO S 4000K
10.14102.0VXXX + 10.34100.1V001
HESS




Design luminaire body made of cast aluminium. Luminaire enclosure made of single-pane safety glass, opens without tools. LIVORNO S: Luminaire for pole top mounting. Fitted with LED up to approx. 53W. LIVORNO XL: Luminaire for pole top and side mounting. For pole top mounted installation, angle of 0° and 5° possible. Fitted with LED up to approx. 107W. 10.34100.1V001 FOR LIVORNO S/SM/XL Wall bracket LIVORNO For luminaire S/SM/XL Made of galvanised steel Spigot ø 76,1 mm Overhanging 250 mm Wall fixation plate 150 x 120 mm Colour: DB 703


Light output 1




1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	5141 lm	Total flux	5141 lm
Luminous efficacy	139 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2588 lm	Total flux	2588 lm
Luminous efficacy	129 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2681 lm	Total flux	2681 lm
Luminous efficacy	134 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		

**1 x LED**


Nominal lamp power	20 W
Lamp flux	2483 lm
Luminous efficacy	124 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	2483 lm
Total power	20 W

**1 x LED**


Nominal lamp power	28 W
Lamp flux	3681 lm
Luminous efficacy	131 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	3681 lm
Total power	28 W

**1 x LED**


Nominal lamp power	28 W
Lamp flux	3441 lm
Luminous efficacy	123 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	3441 lm
Total power	28 W

**1 x LED**


Nominal lamp power	20 W
Lamp flux	2767 lm
Luminous efficacy	138 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	2767 lm
Total power	20 W

**1 x LED**

Nominal lamp power	28 W
Lamp flux	3303 lm
Luminous efficacy	118 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	3303 lm
Total power	28 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

53 W
6604 lm
125 lm/W
4000 K
80

LOR
Total flux
Total power

100%
6604 lm
53 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

37 W
5175 lm
140 lm/W
4000 K
80

LOR
Total flux
Total power

100%
5175 lm
37 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

37 W
5362 lm
145 lm/W
4000 K
80

LOR
Total flux
Total power

100%
5362 lm
37 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

37 W
4966 lm
134 lm/W
4000 K
80

LOR
Total flux
Total power

100%
4966 lm
37 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI


53 W
7361 lm
139 lm/W
4000 K
80

LOR
Total flux
Total power


100%
7361 lm
53 W



1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	6882 lm	Total flux	6882 lm
Luminous efficacy	130 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	7130 lm	Total flux	7130 lm
Luminous efficacy	135 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3565 lm	Total flux	3565 lm
Luminous efficacy	127 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 11.44 in

Width: 4.72 in

Height: 8.48 in

Adjustability

Fixed

Electric

System power: 20-53 W

Protection

IP: 65