Product data sheet

LINE50HEX
LH50H-139302-LXXXO
EGLO



pendant mounted dir-indir LED luminaire;

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.58 W	CRI	90
Total flux	1689 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.58 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.58 W	CRI	90
Total flux	1689 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.58 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.58 W	CRI	90
Total flux	1689 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.58 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.58 W	CRI	90
Total flux	1689 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.58 W

Light output 5 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.58 W	CRI	90
Total flux	1689 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.58 W

Light output 6 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.58 W	CRI	90
Total flux	1689 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	13.58 W

Mounting mode

Pendant

Shape and measurements

Length: 51.42 in

Width: 44.49 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 81.45 W

Protection

IP: 20

Designation labels: CE