Product data sheet


MACARON 4 BOLLARD
MC-10003-T3-W40
LIGMAN



IP 66 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	46.5 W	CRI	80
Total flux	4538 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	100%
		Total power	46.5 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 9.84 in
Width: 9.84 in
Height: 23.62 in
Weight: 4.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 46.5 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C