

Product data sheet

STREET LIGHTING
V1-S1-70496-40L34-6605050 TORNADO PLAZA 50W 5000K
VARTON




IP
66

IK
09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: squares and parkings. Installation: pole and side-entry mounted (Ø48mm-60mm). AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: YXL1 Protection class: I Suitable for top end size, mm: 48...60 Mounting method: Side-entry Ingress protection (IP): IP66 Impact resistance: IK09 Power factor: 0,97 Color rendering index: 70-79 Nominal voltage, V: 220...230
<https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-plaza-dlya-ploshchadi/svetodiodnyy-svetilnik-var-ton-ulichnyy-tornado-plaza-50-vt-kreplenie-na-konsol-5000-k-ral7045-seryy-/>

Light output 1



1 x LED			
Nominal lamp power	50 W	LOR	100%
Lamp flux	7250 lm	Total flux	7250 lm
Luminous efficacy	145 lm/W	Total power	50 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 24.72 in
Width: 10.47 in
Height: 3.90 in

Adjustability

Fixed

Electric

System power: 50 W

Protection

IP: 66
IK: 09