Product data sheet

FUTURA 2.5FT SNS PC AL 8000/840 COR
79083
TREVOS



unique design, resistant against humidity and dust, with IP66 enclosure rating and built-in aluminium heat sinks; optimal mounting height: 3.5 to 10 m; digitally dimmable. DALI driver with corridor function, microwave motion sensor; Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: translucent PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Clips: polyamide + 15 % fibreglass; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless three-pole terminal block; Power: 48,3 W; Luminaire flux: 7830 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|50 °C; Weight: 3,15 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	48.3 W	CRI	80
Total flux	8330 lm	LOR	100%
Luminous efficacy	172 lm/W	ULOR	4%
		Total power	48.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.17 in
Width: 5.71 in
Height: 4.41 in

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Silver gray, White
Designer: TREVOS

Electric

System power: 48.3 W
Ballast: ECG
Appliance Class: I

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...122°F