


# Product data sheet

WALL MOUNTED LUMINAIRE TOLEDO 660 - WITH EXTERNAL LOUVERS 4000K  
10.01223.0VXXX + 10.41210.0V001  
HESS




Domed luminaire canopy, horizontally separated in two, made of aluminium, underside painted white. Support elements made of aluminium. Cylindrical luminaire enclosure made of PMMA. Round luminaire body made of aluminium, optionally with or without louvers. 10.31201.2V001 PARALLEL ROHRE Bracket TOLEDO 660 double Made of galvanised steel Overhanging 450 mm on each side Spigot pole  $\varnothing$  76,1 mm Colour: DB 703 or all RAL- (classic- single shades), Hess-DB and Hess-Glimmer-colours. RAL pearl-mica-metallic-shades on request.


## Light output 1




1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2823 lm	Total flux	2823 lm
Luminous efficacy	101 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2510 lm	Total flux	2510 lm
Luminous efficacy	90 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2672 lm	Total flux	2672 lm
Luminous efficacy	95 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		


**1 x LED**

Nominal lamp power  
Lamp flux  
Luminous efficacy  
CCT  
CRI

28 W  
2686 lm  
96 lm/W  
4000 K  
80

LOR  
Total flux  
Total power

100%  
2686 lm  
28 W


**1 x LED**

Nominal lamp power  
Lamp flux  
Luminous efficacy  
CCT  
CRI

20 W  
2122 lm  
106 lm/W  
4000 K  
80

LOR  
Total flux  
Total power

100%  
2122 lm  
20 W


**1 x LED**

Nominal lamp power  
Lamp flux  
Luminous efficacy  
CCT  
CRI

20 W  
1888 lm  
94 lm/W  
4000 K  
80

LOR  
Total flux  
Total power

100%  
1888 lm  
20 W


**1 x LED**

Nominal lamp power  
Lamp flux  
Luminous efficacy  
CCT  
CRI

20 W  
2010 lm  
100 lm/W  
4000 K  
80

LOR  
Total flux  
Total power

100%  
2010 lm  
20 W

**1 x LED**

Nominal lamp power  
Lamp flux  
Luminous efficacy  
CCT  
CRI

20 W  
2020 lm  
101 lm/W  
4000 K  
80

LOR  
Total flux  
Total power

100%  
2020 lm  
20 W

**Mounting mode**

Wall mounted

**Shape and measurements**

Length: 46.13 in

Width: 36.75 in

Height: 37.74 in

**Electric**

System power: 20-28 W

**Protection**

IP: 65

Adjustability

Fixed