Product data sheet


LESS IS MORE 50
312307.004
RZB



IP 20 IK 03

Series: LESS IS MORE 50 Linear ceiling and wall luminaire for aesthetically sophisticated lighting. Housing made of extruded aluminium profile, powder-coated. End cap made of aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Suitable for Ceiling mounting. LED unit with integrated converter interchangeable and removable. Suitable for through-wiring. With sensors or as a safety luminaire on request. Colour: silver, matt (approx. RAL 9006) Length: 1407 mm Width: 57 mm Height: 75 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 34 W Rated luminous flux: 3850 lm Beam angle Down: 106° Luminous efficiency: 113 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34 W	CRI	80
Total flux	3850 lm	LOR	62%
Luminous efficacy	113 lm/W	ULOR	18%
		Total power	34 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.24 in
Width: 55.39 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 34 W

Protection

IP: 20
IK: 03