# Product data sheet

MPS8-35MLHE-CW-EDU


CURRENT



IP 48

The MPS linear fixture is a multi purpose solution that will fit seamlessly into countless applications. MPS is adaptable to most any environment.Three lens options as well as less lens (NL), Modular replaceable LED boards and driver accessible for future maintenance or upgrades, Optional SpectraSync™ offers three modes of tunable white solutions and integrates seamlessly into a variety of control systems, NX Lighting Control provides options for standalone and networked integrated sensor with wired or wireless connectivity for NX system deployments, Optional integral emergency battery pack, DLC® (DesignLights Consortium) Qualified,

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3500 K |
| Nominal lamp power | 67.6 W | CRI | 80 |
| Total flux | 9081 lm | LOR | 100% |
| Luminous efficacy | 134 lm/W | ULOR | 8% |
| | | Total power | 67.6 W |

### Mounting mode

Ceiling mounted, Pendant

### Shape and measurements

Length: 2.99 in
Width: 95.98 in
Height: 1.57 in

### Adjustability

Fixed

### Design

Color of housing: Black, White, Silver gray

### Electric

System power: 67.6 W

### Protection

IP: 48