

Product data sheet


LUNOVA 830 CLO CL2
303638
FAGERHULT



IP
66

Installation Luminaire for assembly on a post, with post top Ø 60 mm or Ø 76 mm. Connection Supplied with 6 m connection cable (H05RN-F). Design Body and heat sink of cast aluminium with stainless steel details. Diffuser of impact and UV-resistant acrylic. Ballast integrated in the luminaire. Reflector Pressure-turned white-enamelled aluminium reflector. Dimming Available with a number of different light regulation options. Miscellaneous Projected wind shield 0,086m². Designed by White Design - Torbjörn Eliasson and Andreas Sture. Standard Colour Anthracite grey (Gris 900 Sablé). Other colours with additional number: Alugrey (RAL 9006) -236. Black (RAL 9005) -230. White (RAL 9010) - 311.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	43 W	CRI	80
Total flux	3000 lm	LOR	100%
Luminous efficacy	70 lm/W	ULOR	7%
		Total power	43 W

Mounting mode

Pole top mounted

Electric

System power: 43 W

Shape and measurements

Length: 21.75 in

Width: 21.75 in

Height: 10.97 in

Protection

IP: 66

Adjustability

Fixed

Design

Color of housing: Black, Silver gray, White