Product data sheet


WALL MOUNTED LUMINAIRE TOLEDO 660 - WITH LOUVERS ASY34 16LED 2200K
88.01200.0V002 + 10.41210.0V001
HESS



IP 65


Domed luminaire canopy, horizontally separated in two, made of aluminium, underside painted white. Support elements made of aluminium. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium, optionally with or without louvres. Wall bracket TOLEDO 660 Made of galvanised steel Overhanging 630 mm

Light output 1




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	2735 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2735 lm
CCT	2200 K	Total power	27.1 W
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3399 lm	ULOR	100%
Luminous efficacy	100 lm/W	Total flux	3399 lm
CCT	2200 K	Total power	33.9 W
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	2960 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2960 lm
CCT	2200 K	Total power	29.4 W
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2507 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2507 lm
CCT	2200 K	Total power	24.8 W
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2274 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2274 lm
CCT	2200 K	Total power	22.5 W
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2035 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2035 lm
CCT	2200 K	Total power	20.2 W
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1790 lm	ULOR	100%
Luminous efficacy	99 lm/W	Total flux	1790 lm
CCT	2200 K	Total power	18 W
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1539 lm	ULOR	100%
Luminous efficacy	98 lm/W	Total flux	1539 lm
CCT	2200 K	Total power	15.7 W
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1291 lm	ULOR	100%
Luminous efficacy	96 lm/W	Total flux	1291 lm
CCT	2200 K	Total power	13.4 W
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1038 lm	ULOR	100%
Luminous efficacy	94 lm/W	Total flux	1038 lm
CCT	2200 K	Total power	11.1 W
CRI	80		



1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3181 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	3181 lm
CCT	2200 K	Total power	31.6 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 46.13 in
Width: 36.75 in
Height: 37.74 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 65