




Product data sheet

FLAT POLYMERO
311943.002.1
RZB



Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Colour: white Diameter: 300 mm Height: 100 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 83 System power: 12 W Rated luminous flux: 1150 lm Luminous efficiency: 96 lm/W Control gear: AC Strom, dim.Ph.an-/abschnitt Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	80
Total flux	1150 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	14%
		Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in
Diameter: 11.81 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: Black

Glare protection

Glare protection: UGR < 19

Electric

System power: 12 W
Ballast: ECG
Controller: DALI

Protection

IP: 40
IK: 03
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F