Product data sheet

AUGUSTA 6 BOLLARD
AUG-10021-W40
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket and clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18.7 W	CRI	80
Total flux	1328 lm	LOR	100%
Luminous efficacy	71 lm/W	ULOR	100%
		Total power	18.7 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 2.95 in
Width: 10.24 in
Height: 39.37 in
Weight: 5.59 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 18.7 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C