

# Product data sheet

ALU-KREIS  
25202.002  
RZB




IP  
43

IK  
02

Series: Alu-Kreis Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 280, H 120 Lamp: LED Colour Temperature: 6300K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 580lm System power: 16W Beam Angle: 138° Unified Glare Ratio: 17,6 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	6300 K
Nominal lamp power	16 W	CRI	60
Total flux	580 lm	LOR	100%
Luminous efficacy	36 lm/W	ULOR	22%
		Total power	16 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 4.72 in  
Diameter: 11.02 in

## Adjustability

Fixed

## Electric

System power: 16 W

## Protection

IP: 43  
IK: 02