# Product data sheet


VXS/VXM VISION SITE LED VXM-E06-LED-E1-RW-7060 COOPER LIGHTING



() COOPER Ligning Solutions

One-piece heavy-wall, die-cast aluminum housing and door, One flush-mounted quick release latch for tool-less access, Offered standard in 4000K (+/- 275K) CCT and nominal 70 CRI, 120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation, Choice of 12 high efficiency, patent pending AccuLED Optics<sup>™</sup>, Suitable for operation in -40°C to 40°C ambient environments, Proprietary circuit module withstands 10kV of transient line surge, Available in arm- and wall-mount configurations and optional strut rod, Features a five-year limited warranty

## Light output 1 (integrated)



| Lamp type          | LED      | CCT         | 3000 K  |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 150.5 W  | CRI         | 75      |
| Total flux         | 19233 lm | LOR         | 100%    |
| Luminous efficacy  | 128 lm/W | Total power | 150.5 W |

# Mounting mode

Pole top mounted

## Shape and measurements

Length: 2.04 in Width: 12.00 in Height: 0.39 in

#### Adjustability

Fixed

#### Electric

System power: 150.5 W

## Protection

IP: 47