


Product data sheet

PASO2 DLH D190 4/2,5W LED860 230V SSP
60813741
ZUMTOBEL



Ceiling-recessed luminaire for cavity ceilings, circular surround (overlapping); includes cavity installation kit; accent spot with superspot beam pattern, approx. 6°; lamp(s): 4/2.5W (PowerLEDs with lens optic), ±15° tilt, light colour: daylight white (6,000K); power consumption 10W; includes control gear; mains voltage 220-240V 50/60Hz; power connection: 3-pole terminal strip; recessed housing: diecast aluminium in white powder-coated finish; PG cable gland; through-wiring possible; partially frosted glass cover; max. surface temperature of glass panel 35°C; stainless steel surround with Camlock catches (no screws visible); IP65 degree of protection, class of protection I; includes gasket; cavity installation: ceiling thicknesses from 4-30mm; ceiling cut-out: Ø182mm, recessed depth: 207 mm; weight: 2.16 kg; Please note: always use flexible leads e.g. H07RN-F when installing the luminaire

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	99
Total flux	588 lm	LOR	100%
Luminous efficacy	59 lm/W	Total power	10 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 8.35 in
Diameter: 8.23 in
Weight: 2.2 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 10 W
Voltage: 230-240 V AC
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE