
Product data sheet

M20/M26H - SPY 66 92718 DIM5
23328 9215
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M20/M26H - SPY 66 92718 DIM5, available in the colour(s): black, white. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26H - PROFILE, SHIFTLINE M26H + SBL, SPLITLINE M20 - PROFILE, SPLITLINE M20 ST - PROFILE. This luminaire is equipped with LED array 25W / CRI>90 (R9: 60) / 2700K / 2688lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: reflector 18°.

Light output 1




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	25 W	LOR	73%
Lamp flux	2688 lm	Total flux	1955 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail, Wall mounted, Pendant, Wall recessed

Shape and measurements

Length: 0.79 in
Width: 6.69 in
Height: 0.04 in

Electric

System power: 28 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE