Product data sheet

MUSTANG 41 STREET AND AREA LIGHTING LUMINAIRES MS-90291-T4-W40

LIGMAN









- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K Formed sheet aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.5 W	CRI	80
Total flux	4665 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	37.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.5 W	CRI	80
Total flux	4665 lm	LOR	100%
Luminous efficacy	124 lm/W	Total nower	37.5 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 53.94 in Width: 12.68 in Height: 3.54 in Weight: 27.5 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 75 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 54

IK: 07

Surface temperature: 40°C