


# Product data sheet

JUNISTAR SOFT WHITE 830LM 2700K RA 98 TRAILING EDGE DIMMING  
7021989032113  
SG ARMATUREN



Attractive exclusive downlight for indoor or outdoor use, particularly well suited to basic lighting due to its very low unified glare rating. Well integrated LED chip and associated dimmable driver. Made of die-cast powder-coated aluminium, glass diffuser. 42° beam angle. Low recessed downlight with hole size Ø83mm Light distribution Direct Light technic LED (not exchangeable) 11W 2700K Ra 98 SDCM 2 L90/B10 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class II SELV IP54 Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Tempered glass Mounting/Connection Recessed, Indoor / Outdoor Screwless terminal block ax. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

## Light output 1



1 x LED			
Nominal lamp power	11 W	LOR	100%
Lamp flux	830 lm	Total flux	830 lm
Luminous efficacy	75 lm/W	Total power	11 W
CCT	2700 K		
CRI	98		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.70 in

Width: 3.70 in

Height: 2.09 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 11 W

Appliance Class: II

## Protection

IP: 54