Product data sheet

NADJA V (1-ARMED BEADED) 9.870.2036.86

LEIPZIGER LEUCHTEN









Recommended mounting height 4.00 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	44 lm/W	
CCT	2000 K	
CRI	25	

LOR	78%
Total flux	2729 lm
Total power	62 W



1 x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR		
Lamp flux	5600 lm	Total flux		
Luminous efficacy	53 lm/W	Total power		
CCT	2000 K			
CRI	25			

Mounting mode Electric

Pole top mounted System power: 62-83 W

Shape and measurements Protection

Height: 20.08 in IP: 55

Diameter: 20.08 in Designation labels: CE, ENEC, F

78% 4366 lm 83 W