


Product data sheet

RAX 150 U19 WHITE 2290LM 4000K RA>80 DALI
5703821169158
SG ARMATUREN



Recessed LED downlight. Made of fire-resistant polycarbonate. SDCM 2. L90/B10>50,000, Supplied with 3000K/4000K LED. Complete with driver and quick connection between driver and downlight for super quick and simple mounting. Can be mounted to ceiling panels with a thickness of 1–50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector. Light distribution Direct Light technic LED 19W 4000K Ra>80 SDCM 2 L90/B10 >100,000 hrs at Ta=25°C Control/Dimming DALI Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Flame retardant polycarbonate Colour: White Optics: Aluminium Mounting/Connection Recessed (downlight), Indoor Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED			
Nominal lamp power	19 W	LOR	100%
Lamp flux	2290 lm	Total flux	2293 lm
Luminous efficacy	121 lm/W	Total power	19 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.81 in
Width: 6.81 in
Height: 5.79 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W
Appliance Class: I

Protection

IP: 20