Product data sheet


VIEW 900 WHITE 1920LM 3000K RA>90 TRAILING EDGE DIMMING
7021981114312
SG ARMATUREN



IP 20 IK 10

Slim bathroom luminaire for easy mounting over mirror. The luminaire has integrated LED and long life. Light distribution Direct Light technic LED 23W 3000K Ra>90 SDCM 3 L90/B10 >50,000 hrs L80/B10 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP44/IP20 IK10 Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 12, B16: 19, C10: 14, C16: 23

Light output 1



1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	1920 lm	Total flux	1921 lm
Luminous efficacy	84 lm/W	Total power	23 W
CCT	3000 K		
CRI	90		

Mounting mode

Wall mounted

Shape and measurements

Length: 35.20 in
Width: 5.28 in
Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 23 W
Appliance Class: II

Protection

IP: 20
IK: 10