Product data sheet

KREIS
221169.002.1
RZB



IP 43 IK 08

Series: Kreis Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic. Diffuser fastening: spring system. Diffuser: plastic, opal, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 260, H 110 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 1200lm System power: 13W Beam Angle: 143° Number of fittings B10A: 136 Number of fittings B16A: 218 Number of fittings C10A: 136 Number of fittings C16A: 218 Inrush current: 0,15A Unified Glare Ratio: 20,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	22%
		Total power	13 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.33 in
Diameter: 10.24 in

Adjustability

Fixed

Electric

System power: 13 W

Protection

IP: 43
IK: 08