Product data sheet

OGR-IJSKAP-PA04-32LED-4000K-1600LM-9.9W

LIGHTRONICS




IP 65

IK 09

OGR CLASSICAL AND FULL OF CHARACTER Classical luminaires do justice to the character of their settings and are the perfect accompaniment for a historic town or village centre. The OGR (Oude Gracht) luminaire is a lighting solution with its own distinctive character. The OGR and the HOLBEIN defined the appearance of the streets of Amsterdam in the seventies for good reason. The luminaire can be supplied with or without ladder rests and optionally with a copper hood and finial. The classical post-top luminaire is suitable for churchyards, parks, town centres and residential areas. The luminaire is impact-resistant (IK09), and dust-tight and waterproof (IP65).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9.9 W	CRI	70
Total flux	44 lm	LOR	87%
Luminous efficacy	4 lm/W	Total power	9.9 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 3.94 in

Diameter: 21.26 in

Adjustability

Fixed

Design

Material impression: Aluminum, Stainless steel

Color of housing: Green

Electric

System power: 9.9 W

Protection

IP: 65

IK: 09