Product data sheet


BILLUND 2 FOR SWEDEN MARKET STREET AND AREA LIGHTING LUMINAIRES
BIU-90013-SE-SCL-8040-500MA
LIGMAN



IP 66 IK 08

- Lamp LED - CRI Ra 70-80 - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated beforepowder coating ensuring high corrosionresistance - Thermal heat dissipation body - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket- High-efficiency polycarbonate lens - Clear toughened glass- Surge protection 10kV - Optics material PMMA - Length of the supplied cable 10m. - Constant lumen output (CLO) - Night-time dimming

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	77 W	CRI	80
Total flux	8111 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	100%
		Total power	77 W

Mounting mode

Pole integrated, Floor mounted

Shape and measurements

Length: 30.12 in
Width: 15.00 in
Height: 4.65 in
Weight: 10.3 kg

Adjustability

Free

Electric

System power: 77 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C