Product data sheet

ROBUST 2 RECESSED EXTERIOR DOWNLIGHTS RO-80486-T2-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Recessed installation with remote IP65 driver

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	34.6 W	CRI	80
Total flux	3909 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	34.6 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.09 in Diameter: 9.45 in Weight: 3.6 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 34.6 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65 IK: 08

Surface temperature: 40°C