Product data sheet


CIRCULAR DOWNWARD 2 RINGS Ø2000 HORITZONTAL
CS4P-00W9AZRU05
LEDSC4



IP 20

LedsC4 Circular Downward 2 Rings ø2000 Horitzontal CS4P-00W9AZRU05V1 Pendant for indoor use. Structure finish: Black. Diffuser material: Softdiffuser. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 30.69 Product length (mm): 3000 Product width or diameter (mm): 2000 Product height (mm): 5000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 2. Driver brand: MEANWELL. Maximum power of light source: 123.2W. Colour temperature: 3000K. Colour rendering index: 92. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 16214. Real lm/W: 63. Voltage / frequency range: 100-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 258. Power factor: NULL. Dimmable equipment included: 0-10V.


Light output 1



1 x LED

Nominal lamp power	108 W	LOR	100%
Lamp flux	8107 lm	Total flux	8107 lm
Luminous efficacy	75 lm/W	Total power	108 W
CCT	3000 K		
CRI	90		

Light output 2



1 x LED

Nominal lamp power	108 W	LOR	100%
Lamp flux	8107 lm	Total flux	8107 lm
Luminous efficacy	75 lm/W	Total power	108 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 78.74 in
Width: 78.74 in
Height: 1.77 in

Electric

System power: 216 W
Appliance Class: I

Protection

IP: 20

Adjustability

Fixed