



Product data sheet

ECLDISPLAYCRMX_BLACK
ECLDISPLAYCRMXFC_2800K_18DEG
PROLIGHTS



The EclDisplay CRMX series presents an innovative and versatile range of LED spotlights, designed for use in galleries, commercial spaces, and other public venues. These advanced fixtures are distinguished by their refined design and multiple control options, including both wired and wireless protocols. They are adaptable to a variety of applications, thanks to the availability of different sources and optics. Each EclDisplay CRMX unit can be programmed and controlled via RDM, encompassing a comprehensive array of built-in input control protocols such as Wireless CRMX, DMX and local knob dimming. At the heart of the EclDisplay CRMX is a highly efficient 40 W RGB+WarmWhite, LED source, capable of delivering both a Full Colour spectrum and also tuneable White. The fixture's versatility is further enhanced by an extensive range of optional accessories, including profile (zoom and static) or wash lenses and additional optical elements like louvres and snoots. This makes the EclDisplay CRMX not just a lighting fixture, but a comprehensive lighting solution adaptable to a multitude of environments and needs. Main features: Data control through wireless CRMX, RDM, DMX and local knob dimming 40W RGB+WarmWhite LED Multiple lens options: Profile (zoom and static) or wash optics

Light output 1



1 x LED			
Nominal lamp power	25.3 W	LOR	100%
Lamp flux	241 lm	Total flux	241 lm
Luminous efficacy	10 lm/W	Total power	25.3 W
CCT	2884 K		
CRI	96		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 39.37 in
Height: 39.37 in

Adjustability

Rotatable, Tilttable, Free

Electric

System power: 25.3 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE