


Product data sheet

RBXS L32 E3
RUBIX LED SURFACE EMERGENCY
DEXTRA




Rubix Surface - 600x600 Surface mounted luminaire, white powder coated steel body, individual cells with opal surround trim for precise optical control. Individually switched diffused back lit halo. Options: E3 - Emergency control gear (498 lumens output) ST3 - Emergency control gear self test AT3 - Emergency control gear DALI auto test S - Switch Dimming (2x drivers) D - Digital Dimming (DSI) (2x drivers) A - Digital Addressable Lighting Interface (DALI)(2x drivers) H - High Frequency Dimming (Analogue 1-10v)(2x drivers) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence BL - Blue Cell Surround OR - Orange Cell Surround R - Red Cell Surround BK - Black Cell Surround

Light output 1 (integrated, emergency)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | | CCT | 4000 K |
| Nominal lamp power | 4.8 W | CRI | 80 |
| Total flux | 498 lm | LOR | 100% |
| Luminous efficacy | 104 lm/W | ULOR | 4% |
| | | Total power | 4.8 W |

Light output 2 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | | CCT | 4000 K |
| Nominal lamp power | 22.9 W | CRI | 80 |
| Total flux | 2899 lm | LOR | 100% |
| Luminous efficacy | 127 lm/W | ULOR | 4% |
| | | Total power | 22.9 W |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 2.40 in

Electric

System power: 27.7 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Adjustability

Fixed