

Product data sheet


ARNO I LED
9.134.9282.01
LEIPZIGER LEUCHTEN



IP
66

recom. pole height: 5.00m – 16.00m light standards: medium and high lighting requirements lamp: incl. 2 Z LED modules 8 designed to approved Zhaga standard colour temperature: 3.000K warm white or 4.000K neutral white LED gear: depending on the electronic driver: up to 50.000 to 100.000 hours; PL-CP or HBM: CLO mode LED life expectancy: PL-CP or HBM: up to 50.000 to 60.000 hours/L100 resp. 50.000 hours/L80; SMD: up to 50.000 hours/L70 light control: at extra cost: power reduction, dimming or CLEVER LIGHT 10 optical system: computer-optimised reflector for Zhaga LED modules for directed light and wide spacings light distribution: asymmetrical wide beam luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing, to be hinged down wiring: completely wired; incl. 8.00m cable; other lengths on demand installation: for top entry ø 76mm and ø 60mm, inclination 5° resp. 10° or for side entry ø 60mm; dispatch standard: for top entry, 5° accessory: column- and wall bracket, column, pole accessories – to be ordered separately application areas: residential and local distribution roads, main streets, car parks, factory premises, hotels, holiday parks

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	124 W	CRI	70
Total flux	15133 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	124 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 24.21 in
Width: 16.73 in
Height: 5.67 in
Weight: 14 kg

Adjustability

Height adjustable

Electric

System power: 124 W

Protection

IP: 66